


FCLib: A Library for Building Data Analysis and Data Discovery Tools


Wendy S. Koegler & W. Philip Kegelmeyer Sandia National Laboratories, USA

IDA 2005 September 9, 2005 Madrid, Spain











Example: Evaluating Broken Spotwelds



- How many break & when?
- Original method:
 - Plot force vs. time & manually search for zero crossings.
- New method:
 - Fully automated
 - 'Close to' failure measure
 - Used instantaneous model orientation







Motivation



 Application Area: Data discovery (DD) in large-scale (terabyte) finite element simulations with focus on feature-based analysis.


Issues:

- No longer possible to examine all data
- Select/Process regions of interest (ROIs)
- Difficult to move data between tools
- DD is a process

Solution:

- Analysts need more automation
- ... but they still need flexibility





Feature Characterization Library (FCLib)




Toolkit of data analysis building blocks (C library)

Goals:

- Provide variety of simple building blocks that can be composed into complex analyses
- Support feature-based analysis (feature = region of interest)
- Minimize low-level processing (automation)
- Generality applicable to a variety of science domains
- Provide an 'elegant' interface simple but not constrained







Presentation Outline



- Motivation
- Goals
- Toolkit Design
 - Data Model
 - Analysis Building Blocks
- Data Analysis Examples
- Summary & Conclusions



















Dataset = "Can Crush"



Sequence = "Time"; coordinate @Step 25 = 0.0025








Key Features of the Data Model






- Minimal set of abstract data objects
 - Types are deeper in the interface
- Subsets are full-fledged data objects
- Mesh ownership of data
- Time-varying data available per variable instead of per step

- Evaluated data model libraries:
 - Parallel Mesh Object (PMO) by TeraScale
 - Visualization Toolkit (VTK) by Kitware
 - Data Object Library (DOL) by Sandia





Analysis Building Blocks I




- Mesh Topology
 - Get mesh entity children/parents/neighbors




- Segment into separate connected components
- Get skin



- Mesh Geometry (Spatial)
 - Edge lengths/surface areas/region volumes
 - Get mesh entities within bounding box or sphere








Analysis Building Blocks II



- Variable
 - Variable Math
 - Statistics: Min/Max/Mean/StandardDeviation/Sum
 - Decompose vectors into normal & tangent components
 - Threshold: find subset




- Subset
 - Set operations: AND, OR or XOR to get new subset
- Time

10

Feature tracking - track ROIs over time







Presentation Outline




- Motivation
- Goals
- Toolkit Design
 - Data Model
 - Analysis Building Blocks
- Data Analysis Examples
- Summary & Conclusions








Example 1: What's Going on in the Ridges?






Find & Track Features




```
fc loadDataset("cancrush.saf", &dataset);
fc getMeshByName(datatset, "can", &mesh);
fc getSeqVariable(mesh, "eqps", &numStep, &seqVar);
fc createFeatureGroup(&featureGroup);
for (i = 0; i < numStep; i++)
   fc threshold(seqVar[i], ">=", 1.0, &subset);
   fc segment(subset, 0, &numROI, &ROIs);
   fc trackStep(i, numROI, ROIs, featureGroup);
fc writeFeatureGraph(featureGroup, "graph.dot");
```











14 9/8/2005



Analyze the Features




```
fc featureGroup getNumFeature(featureGroup,
                               &numFeature);
for (i = 0; i < numFeature; i++)</pre>
   fc getFeatureROIs(featureGroup, i, &numROI,
                      &stepIDs, &ROIs);
   for (j = 0; j < numROI; j++)
     fc getVariableSubsetMinMax(seqVar[stepIDs[j]],
                 ROIs[i], &mins[i][j], &maxs[i][j]);
     // print stats
```















Example 2: Yet Another Can Crush Study

- Complex assembly
- Need to assess
 - simulations vs. experiments
 - effect of parameters
- Want to predict behavior in even more complex systems
- But what to measure?!
- FCLib = prototyping environment











Analyses In Progress: Dents, Tears & Gaps

- Dents (deformed regions) Subtract translation from general displacement
- Tears (regions of failed elements) Use topology to determine type and if breaks the mesh.
- Gaps (adjacent meshes separate) "Gap lines" mesh.






Summary & Conclusions




 Presented and discussed a data analysis toolkit



Goals:

- Provide variety of simple building blocks than can be composed into complex analyses
- Support feature-based analysis (feature = region of interest)
- Minimize low-level processing (automation)
- Generality applicable to a variety of science domains
- Provide an 'elegant' interface simple but not constrained






Future Plans




- More building blocks & analyses:
 - Dent, gap, & tear
 - Time-based & event
- GUI for analysis composition
- Better integration with viz packages



- Use FCLib for research:
 - "Smart" dataset comparisons using characterized features






Acknowledgements



Ann Gentile, FCDMF Developer



Contact: Wendy (Koegler) Doyle <wkoegle@sandia.gov> http://www.ca.sandia.gov/ASCI/sdm → Data Discovery → FCDMF

This research was supported by the DOE Advanced Strategic Computing Initative (ASCI) Data and Visualization Sciences (DVS) Data Discovery Program.

